



Vertical Stencil Tech Data Sheet

Product Description:

Universal Templates adhesive backed stencil sheets are manufactured in our Nashua, NH facility and made in the USA. The stencil sheets are manufactured from recycled HIPS (High Impact Polystyrene), and within strict quality control guidelines.

Product uses:

Universal Templates stencil sheets are designed for use by a qualified professional in both residential and commercial projects. Our stencils are most commonly used in an EIFS, Stucco or ICF wall finish to create the look and feel of real masonry.

In all EIFS/Stucco, ICF applications, it's important to make sure all walls are smooth and free of surface contaminants, such as dust, dirt, peeling paint, sealers, efflorescence, etc. All of which may impair the adhesion of our stencils to work properly.

Universal Templates stencils are available in a variety of patterns and are .023 thick (unless custom thickness) creating the realistic look of brick or stone.

Color	White, Black Recycled HIPS
Thickness	.023 or custom thickness
Plastic	Recycled HIPS (High Impact Polystyrene)
Adhesive	Water soluble dispersible
Paper	Poly coated wax paper 25#
Operating Temperatures	50° to 90° F

In the EIFS industry Faux Brick is a common finish. This is where the use of an adhesive back stencil is used. The process begins with a standard EIFS system, here's an example of the process. Note: Make sure to follow your manufacturer's directions for all EIFS/Stucco, ICF applications.

Application example:

- We suggest you create a small sample to determine and verify the compatibility of our stencil to the base coat of the wall
- Prep the substrate per project specifications
- Make sure the applied area is dry and no dust exists
- Remove the parchment release paper from the back of the stencil
- Apply the stencil to the wall adhesive side against the surface
- Align stencil to make sure it's in place correctly and has full contact with the surface (Note: Areas of stencil that do not adhere to surface may leak and cause undesirable results)
- Trowel apply the finish coat over the stencil and float to desired texture
- Wait for finish to set up and remove the faux brick stencil (if left on too long it will be hard to remove)
- Stencils cannot be applied in temperatures below 50 ° F or above 90° F
- NOTE: Make sure to follow all manufacturer directions for Stucco, EIFS and ICF wall finishing systems. Note: This was just an example and does not dictate application process

Storage:

- Store in dry area and out of direct sunlight in the original unopened container temperature between 50° F to 90° F (10° C to 32° C).
- Do **NOT** leave stencils outside exposed to the weather elements. This will cause THE ADHESIVE TO FAIL and void any warranty.

Shelf Life:

- 36 months if properly stored in original containers in a dry area away from moisture and excessive heat.

Warranty: Manufacturer limits warranty to (30) days. Seller and manufacturer's obligations under this warranty are limited to the purchase price of that portion of the material proven to be defective. No other warranties are expressed or implied.